

Date: Wednesday, November 13, 2013  
Location: SAN ANTONIO, TX  
Circulation: 29,180  
Type(Frequency): Magazine (5Y)  
Page: 59  
Section: Advances  
Keyword: Lucifer Lighting

## ADVANCES

Product Introductions

### High-Efficacy Performance

The **Bridgelux** Vero series LED arrays have begun shipping with a nominal performance efficacy of 120 lumens per watt (110 lumens per watt minimum), providing an energy savings of 11% over the product's prior generation. The arrays also now are available with a 2SDCM MacAdam option for more precise—and uniform—color control.  
→ Visit [www.bridgelux.com](http://www.bridgelux.com) or **Circle 295**.

*In retail settings, careful consideration must be given to placement, color temperature and fixture aesthetic.*



### 4 Retro-Industrial Option

DesignLights Consortium-approved, Retro Industrial LED Low-Bay fixtures by **YS Lighting** pair high-efficiency LEDs with a vintage appearance and are redesigned for a range of high-ceilinged applications.  
→ Visit [www.yslighting.com](http://www.yslighting.com) or **Circle 299**.

### 5 Industrial-Grade Performance

Kemlux III LED Series fixtures, designed by **Hubbell**, are able to stand up to the rigors posed by corrosive chemical, petrochemical, marine, and power-generation settings. A modular design allows for six mounting options for the luminaires, which function at ambient temperatures ranging from -40°C to 40°C.  
→ Visit [www.hubbellindustrial.com](http://www.hubbellindustrial.com) or **Circle 300**.

### 6 Simple Geometry

**Lucifer Lighting**'s aptly named Cylinder LED Luminaire features a sleek die-cast aluminum body and a power supply integrated into its mounting base. The tapered aperture helps increase lumen efficiency and tool-less adjustment enables up to a 45° tilt and 360° swivel rotation, available in a range of color temperatures, packages and beam optics.  
→ Visit [www.luciferlighting.com](http://www.luciferlighting.com) or **Circle 301**.



[www.architecturalsl.com](http://www.architecturalsl.com)

ARCHITECTURAL SSL • 10.13 • 59