


# 2 SERIES LED SAMPLES


- Adjustable, Fixed, Wallwasher and Wall Grazer
- 2.40" & 1.80" Round apertures and 2.10" Square apertures
- Room-side hot-aim tilt of 45° and 357° locking rotation
- Available in 80+, 90+ & 97+ CRI
- 2700K, 3000K, 3500K and 4000K CCT
- 90+ CRI Warm Dim with 1800K - 3000K CCT range
- High and Low Flux lumen packages
- Proprietary 20°, 40° & 60° field-changeable optics
- Accepts 2 effects devices for optimal design
- Powder Coat, Plated and Custom Finish options
- Flange overlay or flush zero-sightline
- IC, NIC, Airtight, CCEA, Title 24 & Remodel applications




2RA



2SG



2SW



2PS

## SAMPLE ORDERING INFORMATION

TRIM	RATING	FLANGE FINISH	CRI/LED	SOURCE LUMENS	CCT	OPTIC	POWER SUPPLY	ACCESSORY LENS	SAMPLE TYPE
<b>2RA</b> Round Expanded Adjustable <b>2RD</b> Round Expanded Fixed Deep Regress <b>2RP</b> Round Expanded Fixed Shallow Regress <b>2RW</b> Round Expanded Wallwasher <b>2PA</b> Round Pinhole Adjustable <b>2PD</b> Round Pinhole Fixed Deep Regress <b>2PS</b> Round Pinhole Fixed Shallow Regress <b>2PG</b> Round Pinhole Wall Grazer <b>2SA</b> Square Expanded Adjustable <b>2SD</b> Square Expanded Deep Regress <b>2SS</b> Square Expanded Shallow Regress <b>2SG</b> Square Expanded Wall Grazer <b>2SW</b> Square Expanded Wallwasher	1 Dry/Damp 2 Wet (Lens sealed in place)	<b>WH</b> White <b>BK</b> Black <b>AU</b> Cashmere Gold <b>AG</b> Silver <b>PR</b> Primer <b>AB</b> Arch Bronze <b>BB</b> Burnt Bronze <b>SS</b> Stainless Steel <b>IG</b> Industrial Gray <b>PB</b> Polished Bronze <b>MB</b> Matte Bronze <b>CH</b> Chrome <b>CF</b> Custom (Consult Factory)	<b>80CA</b> 80+ CRI  <b>90CA</b> 90+ CRI  <b>97CA</b> 97+ CRI  <b>90WA</b> 90+ CRI	<b>12L</b> 1200lm <b>16L</b> 1600lm <b>23H</b> 2300lm  <b>10L</b> 1000lm <b>14L</b> 1400lm <b>19H</b> 1900lm  <b>10L</b> 1000lm <b>12L</b> 1200lm <b>17H</b> 1700lm  <b>12H</b> 1265lm	<b>1</b> 2700K <b>2</b> 3000K <b>3</b> 3500K <b>4</b> 4000K  <b>1</b> 2700K <b>2</b> 3000K <b>3</b> 3500K <b>4</b> 4000K  <b>1</b> 2700K <b>2</b> 3000K <b>3</b> 3500K <b>4</b> 4000K  <b>W</b> Warm Dim	<b>2</b> 20° <b>3</b> 40° <b>4</b> 60° (Not available for round pinhole) <b>G</b> Wall Grazer Optic (2PG, 2SG only) <b>W</b> Wallwasher Optic (2RW, 2SW only)	<b>Domestic (120V)</b> <b>TR2</b> Philips, 2% Leading/Trailing/Triac (Not available with 80CA12L, 90CA10L, 97CA10L) <b>L23</b> Lutron, Hi-Lume 1% 2-Wire  <b>Universal (120-277V)</b> <b>AN4</b> Philips Xitanium 1% 0-10V, LOG <b>LN2</b> Philips Xitanium 1% 0-10V, LIN <b>EA2</b> eldoLED, SOLOdrive 0.1% 0-10V, LOG <b>LA2</b> eldoLED, SOLOdrive 0.1% 0-10V, LIN	<b>Standard Effects Device</b> <b>04</b> Soft Focus Lens (2" x 2", 2" x 5" only) <b>GL</b> Wall Grazer Lens (2PG, 2SG only) <b>WL</b> Wallwasher Lens (2RW, 2SW only)  <b>Alternate Effects Device</b> <b>00</b> No Lens (Dry/Damp location, Not available with 90WA12H) <b>02</b> Honeycomb Louver (Dry/Damp location, Not available with 90WA12H) <b>03</b> Clear Glass Lens (Not available with 90WA12H) <b>05</b> Frosted Glass Lens <b>09</b> Ultra Violet Lens <b>11</b> Shatterproof Soft Focus Lens <b>12</b> Shatterproof Frosted Lens <b>26</b> Frosted Linear Spread Lens (Dry/Damp location)	<b>HH</b> Hand-Held/Tabletop - Ships with a 6' cord and plug, no dimmer. <b>TDD</b> Triac Dimming Demo - Ships with a 6' cord and plug, and Triac Dimmer. Must be paired with <b>TR2</b> or <b>L23</b> driver. <b>ZDD</b> 0-10V Dimming Demo - Ships with a 6' cord and plug, and 0-10V Dimmer. Must be paired with <b>AN4</b> , <b>LN2</b> , <b>EA2</b> or <b>LA2</b> driver.  <b>SPECIFIED SEPARATELY</b> <b>Standard Demo Case</b> - DC-2S-2019 <b>Full scale mock-up</b> - Order standard housing/trim combinations on the <a href="#">2 Series Spec Sheet</a> . Dimmer and cord and plug provided by contractor, if required.

## ACCESSORIES

### ALTERNATE EFFECTS DEVICES

- ☐ **HCL-2** Honeycomb Louver <sup>1,2</sup>
- ☐ **CGL-2** Clear Glass Lens <sup>2</sup>
- ☐ **SFL-2** Soft Focus Lens
- ☐ **FGL-2** Frosted Glass Lens

<sup>1</sup> Dry/Damp location only

<sup>2</sup> Not for use with 90W12H Warm Dim

- ☐ **UVL-2** Ultra Violet Lens
- ☐ **FLSL-2** Frosted Linear Spread Lens <sup>1</sup>
- ☐ **SFL-2-SP** Shatterproof Soft Focus Lens
- ☐ **FGL-2-SP** Shatterproof Frosted Lens

### ALTERNATE OPTICS

Interchangeable optics accessible through fixture aperture.

- ☐ **RO-50-20-2** 20° optic
- ☐ **RO-50-40-2** 40° optic
- ☐ **RO-50-60-2** 60° optic

Please reference comprehensive [2 Series Spec Sheet](#) for detailed information.



**Declare.**

**LUCIFER®**  
LIGHTING COMPANY

[luciferlighting.com](http://luciferlighting.com)

©2022 Lucifer® Lighting Company

As part of its policy of continuous research and product development, the company reserves the right to change or withdraw specifications without prior notice.

[PH] +1-210-227-7329  
[FAX] +1-210-227-4967

pg. 1

[DATE OF REV: 11282022]